



SIGNS
BY TOMORROW
SIGNS & GRAPHICS NATIONWIDE
Arlington Heights • IL



HP Durable Frontlit Scrim Banner is a mid-priced, 16-oz. durable media delivering high-colour brilliance and image quality on a smooth matte finish. Fire-resistant and reflective qualities make it a great choice for indoor use¹.

Ideal for mid-volume print service providers (PSP) looking for well-priced indoor banner with a high-quality look.

Durable and fire-resistant (NFPA 701/B1/M2) PVC scrim banner fits a range of indoor and outdoor applications where high visibility and impact are desired.

This PVC frontlit scrim banner has a high-quality matte finish that renders high image definition and vivid colour for maximum impact. Smooth surface provides good ink adhesion and renders brilliantly sharp images.

HP Durable Frontlit Scrim Banner is perfect for a wide range of indoor or outdoor displays; this breadth of applications makes it an exceptionally versatile media.

¹ Meets the following fire-resistant ratings: NFPA 701 (USA) B1/DIN 4102 (Germany) and M2/NFP 92-501 (France)

HP Durable Frontlit Scrim Banner

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

| Weight | 535 g/m ² per ISO 536 Test Method, 16 oz. | | | | | | | | | | | | | | | |
|--|--|-----------------|------------|-----------|--------|------------------|--------------|--------|------------------|--------------|--------|------------------|--------------|--------|-------------------|--------------|
| Thickness | 17.7 mil/450 microns per ISO 534 Test Method | | | | | | | | | | | | | | | |
| Opacity | Greater than or equal to 96% per ISO 2471 Test Method | | | | | | | | | | | | | | | |
| Lamination | Lacqering possible | | | | | | | | | | | | | | | |
| Finish | Semi-gloss | | | | | | | | | | | | | | | |
| Tear strength | >100N (MD) / >110N (CD) per ASTM D1004 Test Method | | | | | | | | | | | | | | | |
| Tensile strength | >1800N/50mm (MD) / >1800N/50mm (CD) per TAPPI T-494 Test Method | | | | | | | | | | | | | | | |
| Operating temperature | 15 to 30° C | | | | | | | | | | | | | | | |
| Operating humidity | 30 to 80% RH | | | | | | | | | | | | | | | |
| Lighfastness (Indoor Commercial Window Low-solvent Ink) | Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence . | | | | | | | | | | | | | | | |
| Flame Retardant | Yes, NFPA 701 (USA) B1 / DIN 4102 (Germany); M2 / NFP 92-501 (France) | | | | | | | | | | | | | | | |
| Waterfastness | Water-resistant | | | | | | | | | | | | | | | |
| Dry time | Less than 15 minutes with HP Designjet 9000 Printer series (@ 23°C, 50% RH). External dryer usage recommended. | | | | | | | | | | | | | | | |
| Shelf time | 1 year, unopened in original packaging | | | | | | | | | | | | | | | |
| Storage temperature | 0 to 40° C | | | | | | | | | | | | | | | |
| Storage humidity | 5 to 95% RH | | | | | | | | | | | | | | | |
| Country of origin | 5 to 95% RH | | | | | | | | | | | | | | | |
| Ordering information | <table><thead><tr><th>Product Numbers</th><th>Roll Sizes</th><th>UPC Codes</th></tr></thead><tbody><tr><td>CG439A</td><td>42 in. x 115 ft.</td><td>883585620029</td></tr><tr><td>CG440A</td><td>54 in. x 115 ft.</td><td>883585620036</td></tr><tr><td>CG441A</td><td>61 in. x 115 ft.</td><td>883585620043</td></tr><tr><td>CG442A</td><td>104 in. x 164 ft.</td><td>883585620050</td></tr></tbody></table> | Product Numbers | Roll Sizes | UPC Codes | CG439A | 42 in. x 115 ft. | 883585620029 | CG440A | 54 in. x 115 ft. | 883585620036 | CG441A | 61 in. x 115 ft. | 883585620043 | CG442A | 104 in. x 164 ft. | 883585620050 |
| Product Numbers | Roll Sizes | UPC Codes | | | | | | | | | | | | | | |
| CG439A | 42 in. x 115 ft. | 883585620029 | | | | | | | | | | | | | | |
| CG440A | 54 in. x 115 ft. | 883585620036 | | | | | | | | | | | | | | |
| CG441A | 61 in. x 115 ft. | 883585620043 | | | | | | | | | | | | | | |
| CG442A | 104 in. x 164 ft. | 883585620050 | | | | | | | | | | | | | | |
| Warranty | HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller. | | | | | | | | | | | | | | | |

© 2008 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

4AA2-4776ENW

