



SIGNS
BY TOMORROW

SIGNS & GRAPHICS NATIONWIDE

Arlington Heights • IL



HP Mesh Banner is a wind-resistant mesh PVC scrim banner with removable liner. Ideal for buildings and outdoor advertising – this weldable scrim banner provides outstanding image quality and high print performance at a competitive price.

Ideal for mid-volume print service providers (PSPs) looking for a versatile mesh scrim banner compatible with HP Latex and low-solvent inks.

Get high image definition and excellent print performance to ensure maximum impact and visibility for outdoor advertising. This media displays high colour brilliance on a wide range of indoor and outdoor applications.

HP Mesh Banner combines excellent handleability with tear-resistance. It is lightweight and weldable, yet durable enough to withstand windy conditions - ideal for outdoor displays and building murals.

Durable and fire-resistant (NFPA 701/B1/M2) HP Mesh banner fits a range of outdoor applications where high visibility and impact are desired¹.

¹ Meets the following fire-resistant ratings: NFPA 701 (US) B1/DIN 4102 (Germany) and M2/NFP 92-501 (France)

HP Mesh Banner

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight (without liner)	355 g/m ² (without liner) per ISO 2286-2 Test Method		
Weight (with liner)	505 g/m ² (with liner) per ISO 536 Test Method, 10.5 oz.		
Thickness	19.7 mil/500 microns (without liner), 22.8 mil/580 microns (with liner) per ISO 20534 Test Method		
Mounting	Welding, grommeting, D-rings		
Finish	Semi-gloss		
Tear strength	>75N (MD) / >80N (CD) per ASTM D1004 Test Method		
Tensile strength	>1300 (MD) / >1500N (CD) per TAPPI T-494 Test Method		
Operating temperature	15 to 35° C		
Operating humidity	30 to 80% RH		
Lighfastness (Indoor Commercial Window Low-solvent Ink)	Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence .		
Flame Retardant	Yes, NFPA 701 (US) B1/ DIN 4102 (Germany); M1 / NFP 92-501 (France)		
Waterfastness	Water-resistant		
Dry time	Less than 10 minutes (@ 23°C, 50% RH)		
Shelf time	1 year, unopened in original packaging		
Storage temperature	0 to 40° C		
Storage humidity	5 to 95% RH		
Country of origin	Product of Saudi Arabia		
Ordering information	Product Numbers	Roll Sizes	UPC Codes
	CG431A	42 in. x 82 ft.	883585618750
	CG432A	61 in. x 82 ft.	883585618767
	CG433A	104 in. x 164 ft.	883585618774
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2008 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material,
visit <http://www.hp.com/go/designjet/supplies>

4AA2-4778ENW

