

# HP Outdoor Frontlit Scrim Banner



**SIGNS**  
BY TOMORROW  
SIGNS & GRAPHICS NATIONWIDE  
Arlington Heights • IL



**HP Outdoor Frontlit Scrim Banner is competitively priced and ideal for wide-ranging outdoor uses. The composition of layered PVC over mesh delivers very good handleability and offers no-hassle post-processing.**

**Ideal for mid-volume print service providers (PSPs) looking for a competitively priced and versatile scrim banner.**

The versatile, temperature-resistant material composition of this frontlit scrim banner ensures great print and post-processing without sacrificing the durability desired for outdoor applications.

HP Outdoor Frontlit Scrim Banner is competitively priced and decreases post-processing hours and cost. Minimise reprints – get durable material construction designed to withstand harsh weather conditions without fading or losing vibrancy.

This durable PVC scrim banner is a certified fire-resistant (B1) media<sup>1</sup>. Designed to withstand harsh weather conditions, it is ideal for a range of outdoor applications, and can be used with HP Latex and low-solvent inks.

<sup>1</sup>Meets the following fire-resistant ratings: B1 / DIN 4102 (Germany)

# HP Outdoor Frontlit Scrim Banner

## Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

For the latest ICC/media profiles, please visit [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies) (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

## Product specifications

<b>Weight</b>	440 g/m <sup>2</sup> per ISO 536 Test Method, 13 oz.															
<b>Thickness</b>	15 mil/380 microns per ISO 534 Test Method															
<b>Opacity</b>	Greater than 97% per ISO 2471 Test Method															
<b>Lamination</b>	Lacqering possible															
<b>Mounting</b>	Sew, grommet, moderately weldable, D rings															
<b>Finish</b>	Semi-gloss															
<b>Tear strength</b>	>50 N (MD) / >45N (CD) per ISO 13934-2 Test Method															
<b>Tensile strength</b>	>1100 N/50mm (MD) / >800N/50mm (CD) per ISO 1421 Test Method															
<b>Operating temperature</b>	15 to 30° C															
<b>Operating humidity</b>	30 to 80% RH															
<b>Lightfastness (Indoor Commercial Window) Low-solvent Ink</b>	Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: <a href="http://www.hp.com/go/supplies/printpermanence">http://www.hp.com/go/supplies/printpermanence</a> .															
<b>Flame Retardant</b>	Yes, B1 / DIN 4102 (Germany)															
<b>Waterfastness</b>	Water-resistant															
<b>Dry time</b>	Less than 10 minutes with the HP Designjet 8000, 9000 and 10000 Printer series (@ 23°C, 50% RH); not applicable with the HP Designjet L65500															
<b>Shelf time</b>	1 year, unopened in original packaging															
<b>Storage temperature</b>	0 to 40° C															
<b>Storage humidity</b>	5 to 95% RH															
<b>Country of origin</b>	Product of China															
<b>Ordering information</b>	<table><thead><tr><th>Product Numbers</th><th>Roll Sizes</th><th>UPC Codes</th></tr></thead><tbody><tr><td>CG409A</td><td>42 in. x 115 ft.</td><td>883585617050</td></tr><tr><td>CG410A</td><td>54 in. x 115 ft.</td><td>883585617067</td></tr><tr><td>CG411A</td><td>61 in. x 115 ft.</td><td>883585617074</td></tr><tr><td>CG412A</td><td>104 in. x 164 ft.</td><td>883585617081</td></tr></tbody></table>	Product Numbers	Roll Sizes	UPC Codes	CG409A	42 in. x 115 ft.	883585617050	CG410A	54 in. x 115 ft.	883585617067	CG411A	61 in. x 115 ft.	883585617074	CG412A	104 in. x 164 ft.	883585617081
Product Numbers	Roll Sizes	UPC Codes														
CG409A	42 in. x 115 ft.	883585617050														
CG410A	54 in. x 115 ft.	883585617067														
CG411A	61 in. x 115 ft.	883585617074														
CG412A	104 in. x 164 ft.	883585617081														
<b>Warranty</b>	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.															

© 2008 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material,  
visit <http://www.hp.com/go/designjet/supplies>

4AA2-4779ENW

