

HP Permanent Matte Adhesive Vinyl



SIGNS
BY TOMORROW

SIGNS & GRAPHICS NATIONWIDE

Arlington Heights • IL



HP Permanent Matte Adhesive Vinyl is an affordable, highly opaque adhesive media with a matte finish, providing bright and vivid colours. The permanent adhesive removes cleanly.

Ideal for mid-volume print service providers (PSPs) looking for well-priced, high-quality self-adhesive vinyl.

HP Permanent Matte Adhesive Vinyl is suitable for a wide range of indoor and outdoor applications like murals, advertisements, POP/POS and event signage. Matte surface captures vibrant graphic detail and displays brilliant, lasting colours.

Highly opaque media offers a durable, high-quality look and fits a wide variety of application needs. Get optimal results on HP Latex printers. It offers weather-resistance with no additional lamination.

This 3.5 mil self-adhesive vinyl maintains a high-quality look across a wide range of indoor and outdoor applications. Permanent adhesive provides strong adhesion and is easily removable.

HP Permanent Matte Adhesive Vinyl

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

| Weight (with liner) | 270 g/m ² per ISO 536 Test Method | | | | | | | | | | | | | | | |
|--|---|-----------------|------------|-----------|--------|------------------|--------------|--------|------------------|--------------|--------|------------------|--------------|--------|------------------|--------------|
| Weight (without liner) | 145 g/m ² per ISO 536 Test Method | | | | | | | | | | | | | | | |
| Thickness (with liner) | 9.4 mil/230 microns per ISO 534 Test Method | | | | | | | | | | | | | | | |
| Thickness (without liner) | 3.5 mil/90 microns per ISO 534 Test Method | | | | | | | | | | | | | | | |
| Opacity | Greater than 95% per TAPPI T-425 Test Method | | | | | | | | | | | | | | | |
| Lamination | Yes | | | | | | | | | | | | | | | |
| Finish | Matte | | | | | | | | | | | | | | | |
| Tensile strength | >40 MD / >40 CD per ASTM D882 2 Test Method | | | | | | | | | | | | | | | |
| Adhesive backing | Permanent with clean removability performance. Solvent based | | | | | | | | | | | | | | | |
| Operating temperature | 15 to 30° C | | | | | | | | | | | | | | | |
| Operating humidity | 30 to 80% RH | | | | | | | | | | | | | | | |
| Lightfastness (Indoor Commercial Window) Low-solvent Ink | Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence . | | | | | | | | | | | | | | | |
| Waterfastness | Water-resistant | | | | | | | | | | | | | | | |
| Dry time | Less than 6 minutes (@ 23°C, 50% RH) | | | | | | | | | | | | | | | |
| Shelf time | 1 year, unopened in original packaging | | | | | | | | | | | | | | | |
| Storage temperature | 0 to 40° C | | | | | | | | | | | | | | | |
| Storage humidity | 5 to 95% RH | | | | | | | | | | | | | | | |
| Country of origin | Product of United States | | | | | | | | | | | | | | | |
| Ordering information | <table><thead><tr><th>Product Numbers</th><th>Roll Sizes</th><th>UPC Codes</th></tr></thead><tbody><tr><td>CG453A</td><td>42 in. x 150 ft.</td><td>883585623044</td></tr><tr><td>CG454A</td><td>54 in. x 150 ft.</td><td>883585623051</td></tr><tr><td>CG455A</td><td>60 in. x 150 ft.</td><td>883585623068</td></tr><tr><td>CG456A</td><td>60 in. x 300 ft.</td><td>883585623075</td></tr></tbody></table> | Product Numbers | Roll Sizes | UPC Codes | CG453A | 42 in. x 150 ft. | 883585623044 | CG454A | 54 in. x 150 ft. | 883585623051 | CG455A | 60 in. x 150 ft. | 883585623068 | CG456A | 60 in. x 300 ft. | 883585623075 |
| Product Numbers | Roll Sizes | UPC Codes | | | | | | | | | | | | | | |
| CG453A | 42 in. x 150 ft. | 883585623044 | | | | | | | | | | | | | | |
| CG454A | 54 in. x 150 ft. | 883585623051 | | | | | | | | | | | | | | |
| CG455A | 60 in. x 150 ft. | 883585623068 | | | | | | | | | | | | | | |
| CG456A | 60 in. x 300 ft. | 883585623075 | | | | | | | | | | | | | | |
| Warranty | HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller. | | | | | | | | | | | | | | | |

© 2008 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

4AA2-4781ENW

